


COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

| MODEL DATA - FOR COMPRESSED AIR | | | |
|---------------------------------|---|--------------------------------|--|
| 1 | Manufacturer: ABC, Inc. | | |
| 2 | Model Number: 1A2B 37kW | Date: | 09/10/18 |
| | <input checked="" type="checkbox"/> Air-cooled <input type="checkbox"/> Water-cooled <input type="checkbox"/> Lubricated <input type="checkbox"/> Oil Free | Type: | Screw |
| | | | # of Stages: |
| 3* | Full Load Operating Pressure ^b | 125 | psig ^b |
| 4 | Drive Motor Nominal Rating | 50 | hp |
| 5 | Drive Motor Nominal Efficiency | 94.1 | percent |
| 6 | Fan Motor Nominal Rating (if applicable) | 1 | hp |
| 7 | Fan Motor Nominal Efficiency | 82.5 | percent |
| 8* | Input Power (kW) | Capacity (acfm) ^{a,d} | Specific Power (kW/100 acfm) ^d |
| | 46.5 | 241 | 19.29 |
| | 38.5 | 201 | 19.15 |
| | 32.9 | 169 | 19.47 |
| | 20.0 | 96 | 20.83 |
| 9* | Total Package Input Power at Zero Flow ^{c, d} | | 0.0 kW |
| 10 |  <p style="text-align: center; font-size: small;"> Note: Graph is only a visual representation of the data in Section 8 Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity </p> | | |

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



Member

- NOTES:
- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
 - The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
 - No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
 - Tolerance is specified in ISO 1217, Annex E, as shown in table below:
NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

| Volume Flow Rate at specified conditions | | Volume Flow Rate | Specific Energy Consumption | No Load / Zero Flow Power |
|--|-----------------------|------------------|-----------------------------|---------------------------|
| m ³ / min | ft ³ / min | % | % | % |
| Below 0.5 | Below 17.6 | +/- 7 | +/- 8 | |
| 0.5 to 1.5 | 17.6 to 53 | +/- 6 | +/- 7 | |
| 1.5 to 15 | 53 to 529.7 | +/- 5 | +/- 6 | +/- 10% |
| Above 15 | Above 529.7 | +/- 4 | +/- 5 | |

ROT 031.2

12/19 R3

This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.